

GAS SOLENOID VALVE



Image for illustration purposes only.

| OVERVIEW |

This Class "A" direct acting, normally closed Gas Solenoid Valve can be used in conjunction with any GasGuard panel for low pressure isolation, proving and interlocking systems. The twin port design (excluding 1/2") allows easy installation of the Flamefast Pressure Transmitter or CPI switches.

Exact specification and manufacturer may vary.

Technical Specification

Power Supply	230VAC 50Hz
Body Material	Aluminium
Internal Material	Aluminium
Seal Material	NBR
Media Temp	-10°C to 90°C
IP Rating	IP54
Approval	CE, UKCA, EN161

Part Numbers & Options/Accessories

Part No	Description
SV15	1/2" Gas Solenoid Valve (230V)
SV20	3/4" Gas Solenoid Valve (230V)
SV25	1" Gas Solenoid Valve (230V)
SV32	1 1/4" Gas Solenoid Valve (230V)
SV40	1 1/2" Gas Solenoid Valve (230V)
SV50	2" Gas Solenoid Valve (230V)
SV65	2 1/2" Gas Solenoid Valve (230V)
SV80	3" Gas Solenoid Valve (230V)
SV100	4" Gas Solenoid Valve (230V)
SV150	6" Gas Solenoid Valve (230V)
SV150E	6" Gas Solenoid Valve (230V) - Electro-hydraulic

LARGER SIZES AVAILABLE ON REQUEST